



Patterson-Kelley

Storage Tanks



Small Volume Jacketed and Insulated

Designed for moderate and commercial peak demands, jacketed storage tanks are available in 80, 120, and 200 gallon capacities. They meet a variety of hot water requirements in smaller commercial applications where a large volume output is required in a short period of time.

SPECIFICATIONS

MODEL NUMBERS	DIAMETER (IN.)	ORIENTATION	HEIGHT (IN.)	MATERIAL	PRESSURE (PSI)	CAPACITY (U. S. GAL.)
DVTG100080	24	VERTICAL	59 ¾	GLASS-LINED	150	80
DVTG100119	28	VERTICAL	63 ½	GLASS-LINED	150	119
DVTG100200	32	VERTICAL	78	GLASS-LINED	150	200

All dimensions and specifications within are subject to change without notice in accordance with our policy of continuous product improvement.

*Vitraglas® is a registered trademark of Niles Steel Tank
NURO® is a registered trademark of Harsco Industrial Patterson-Kelley

STANDARD FEATURES

- ✓ ASME Construction
- ✓ Designed for Storage of Potable Water to 180°F
- ✓ 80, 120, and 200 Gallon Capacities
- ✓ Vitraglas® Lining
- ✓ Hand Hole Cleanout
- ✓ Low Restriction Brass Drain Valve
- ✓ Side T&P Valve Opening
- ✓ Two Protective Magnesium Anode Rods
- ✓ Non-CFC Foam Insulation
- ✓ 5-Year Limited Tank Warranty

APPLICATIONS

- Dormitories and laundry facilities
- Restaurants and kitchens
- Designed to work with Patterson-Kelley NURO® equipped water heating equipment.*

Harsco Industrial Patterson-Kelley
155 Burson Street
East Stroudsburg, PA 18301
www.harscopk.com

Phone: 570.476.7261
Toll Free: 877.728.5351
Fax: 570.476.7247

1004905916 Rev B Jun-2017



Patterson-Kelley

Storage Tanks



Large Volume Jacketed and Insulated

Available in 34” and 40” standard diameters, these large volume, insulated, and jacketed tanks offer capacities ranging from 210-415 gallons. Two-inch, high-density foam insulation minimizes heat loss.

SPECIFICATIONS

MODEL NUMBERS	DIAMETER (IN.)	ORIENTATION	Vertical Tank Height/ Horizontal Tank Length (in.)	MATERIAL	PRESSURE (PSI)	CAPACITY (U. S. GAL.)
DHTD000210	34	HORIZONTAL	79	DOUBLE-LINED	125	210
DHTD100210	34	HORIZONTAL	79	DOUBLE-LINED	150	210
DHTG000210	34	HORIZONTAL	79	GLASS-LINED	125	210
DHTG100210	34	HORIZONTAL	79	GLASS-LINED	150	210
DHTD000320	34	HORIZONTAL	115	DOUBLE-LINED	125	320
DHTD100320	34	HORIZONTAL	115	DOUBLE-LINED	150	320
DHTG000320	34	HORIZONTAL	115	GLASS-LINED	125	320
DHTG100320	34	HORIZONTAL	115	GLASS-LINED	150	320
DVTD000320	34	VERTICAL	119	DOUBLE-LINED	125	320
DVTD100320	34	VERTICAL	119	DOUBLE-LINED	150	320
DVTG000320	34	VERTICAL	119	GLASS-LINED	125	320
DVTG100320	34	VERTICAL	119	GLASS-LINED	150	320
DHTD000415	40	HORIZONTAL	106	DOUBLE-LINED	125	415
DHTD100415	40	HORIZONTAL	106	DOUBLE-LINED	150	415
DHTG000415	40	HORIZONTAL	106	GLASS-LINED	125	415
DHTG100415	40	HORIZONTAL	106	GLASS-LINED	150	415
DVTD000415	40	VERTICAL	110	DOUBLE-LINED	125	415
DVTD100415	40	VERTICAL	110	DOUBLE-LINED	150	415
DVTG000415	40	VERTICAL	110	GLASS-LINED	125	415
DVTG100415	40	VERTICAL	110	GLASS-LINED	150	415

All dimensions and specifications within are subject to change without notice in accordance with our policy of continuous product improvement.

STANDARD FEATURES

- ✓ Horizontal or Vertical Configurations Available
- ✓ Available with Vitraglas® Lining or Double Vitraglas® Lining
- ✓ Sturdy Steel Jacket
- ✓ Hand Hole Cleanout and Manway – Optional
- ✓ Designed for Storage of Potable Water up to 180°F
- ✓ All Tanks are Constructed and Certified in Accordance with ASME Section IV, Part HLW for 125 psi (862 kPa)
- ✓ Two Female 3” NPT Water Connections
- ✓ Two 3/4” NPT Aquastat Fittings
- ✓ Magnesium Anode Rods
- ✓ 2” High Density Foam Insulation
- ✓ 5-Year Limited Warranty on Steel Tank
- ✓ 10-Year Limited Warranty on Double Vitraglas® lined Steel Tank

APPLICATIONS

- Large fitness centers, industrial plants, hotels, stadiums, and resorts

*Vitraglas® is a registered trademark of Niles Steel Tank
NURO® is a registered trademark of Harsco Industrial Patterson-Kelley

Harsco Industrial Patterson-Kelley
155 Burson Street
East Stroudsburg, PA 18301
www.harscopk.com

Phone: 570.476.7261
Toll Free: 877.728.5351
Fax: 570.476.7247

1004905916 Rev B Jun-2017